

REFRIGERATED COMPRESSED AIR DRYER

MODEL:

ED 5300 400/3/50

Rated capacity

RATED CAPACITY

m ³ /h	5300
l/min	88333
cfm	3118

Power supply

V/Ph/Hz	400/3/50
---------	----------

Power consumption

KW	9,52
----	------

Full Load cons.

KW	15,14
----	-------

Rated absorpt.

Ampere	17,6
--------	------

Full Load Ampere

Ampere	24,9
--------	------

Lock. Rotor Ampere

Ampere	145
--------	-----

Weight

Kg / Lbs	620
----------	-----

Air connection

IN/OUT	DN 150
--------	--------

Coolant type

Freon	R407C
-------	--------------

Inlet air temp.

°C / °F	35 / 95	(Max 55 / 131)
---------	---------	----------------

Outlet air temp.

°C / °F	25 / 77	(Max 40 / 104)
---------	---------	----------------

Ambient temp.

°C / °F	25 / 77	(Max 45 / 113)
---------	---------	----------------

Working pressure

bar / psi	7 / 100	(Max 13 / 189)
-----------	---------	----------------

Pressure drop

bar / psi	0,3 / 4,35	(Max 0,34 / 5)
-----------	------------	----------------

Pressure dew point

°C / °F	3/37°	ISO CLASS 4
---------	-------	-------------

Standard features

- Control panel:** *Electronic system type*
- Condenser cooling:** *Air cooled*
- Ventilator motor:** *Suction fan*
- Heat exchanger:** *Aluminium brazed plate*
- Expansion method:** *Capillary tube + by-pass*
- Separator type:** *Demister type*
- Compressor type:** *Hermetic type*
- Installation location:** *Indoor*
- Drain discharge:** *No loss drain*
- Electric protection:** *IP 42*

Performances refer to air suction of FAD 20°C (68°F), 1 bar (1 4.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37.4°F) pressure dewpoint, 2 5°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

